

## Amendments to the Specification

### Abstract of the Disclosure

Please replace the abstract with the following rewritten abstract:

B<sup>1</sup>

The invention relates to a surgical implant that provides an artificial diarthroidal-like joint, suitable for use in replacing any joint, but particularly suitable for use as an intervertebral disc endoprosthesis. The invention contains two rigid opposing shells, each having an outer surface adapted to engage the surfaces of the bones of a joint in such a way that the shells are immobilized by friction between their outer surfaces and the surfaces of the bone. These outer surfaces are sufficiently rough, while ~~that large frictional forces strongly resist any slippage between the outer surface and the bone surfaces in the joint.~~ They may be convex, and when inserted into a milled concavity, are immediately mechanically stable. Desirably, the outer surfaces of the shells are adapted to allow for bony ingrowth, which further stabilizes the shells in place. The ~~the~~ inner surfaces of the shells are relatively smooth, ~~and adapted to slide easily across a portion of the outer surface of a central body disposed between the shells.~~ The central body has a shape that cooperates with the shape of the inner surface of the shell so as to provide a range of motion similar to that provided by a healthy joint. ~~A flexible sheath extends between edges of the opposing shells. The inner surface of this sheath, together with the inner surfaces of the rigid shells, defines a cavity encasing the central body. At least a portion of this cavity is filled with a fluid lubricant, further decreasing the frictional force between inner surfaces of the shell and the surface of the central body.~~

### Detailed Description of Specific Embodiments

Please replace the second paragraph on page 19 of the application with the following rewritten paragraph:

B<sup>2</sup>

As shown best in FIG. 67, central body 60 is a preferably a donut-shaped structure, and includes a convex upper contact surface 94, a convex lower contact surface 96, and a central axial opening 98. In addition, central body member 60 preferably includes an upper shoulder 92 and a lower shoulder 90. Each shoulder 90, 92 consists of an indentation in the surface of the central body member which defines a ledge that extends around the circumference of the central body 60.